

Makita®

Self-Levelling Rotation Laser

SKR200



Product Overview



Product Specification Sheet



Diameter of Laser Point	6mm @ 10m
Measuring Tolerance	± 1.0mm/10m
Range	200m Diameter (Rotating) 30m (Plumb Beam)
Operating Temperature Range	-10° - 50°C
Power Source	2x 1.5V LR20 (D-Batteries)
Operating Time	Up to 60 Hours
Overall Length	197mm
Net Weight	1.6kg

- **Red Beam** – The SKR200 features a red laser beam accurate to ±1mm at 10m.
- **Plumb Beam** – The rotation can be ceased allowing the SKR200 to be used as a plumb laser with a range up to 30m, the plumb dot can be moved with the remote control.
- **Self Levelling** – The unit is capable of self levelling ±6° allowing the SKR200 to be used on uneven surfaces.
- **H.I. Alert Mode** - If the laser is moved during H.I. alert mode, the laser beam is deactivated and all 3 LEDs blink red, for example if the laser is bumped during operation. Switch the laser off and on again to continue.
- **Battery Powered** – The SKR200 is powered by 2x D-sized batteries offering 60 hours of runtime.
- **Moveable Head** – Once the rotation has been ceased the laser head can be moved so the plumb dot can be positioned where required.
- **200m Usable Range** – In rotation mode, the range of the SKR200 is up to 200 metres when coupled with the laser receiver.
- **Manual Mode** - Allows users to set a grade up to 6 degrees, useful when setting plumbing pipe or driveway so there is a consistent slope.
- **Variable Rotation Speed** – The rotation speed can be slowed and ceased if required with the remote control.

Advantages

Range



Bright red laser with a range up to 30m (plumb mode) or 200m (rotation – with receiver).

Accuracy



Accurate to $\pm 1.0\text{mm}$ @ 10m.

Convenience



Ability to slow rotation or cease as required.

Compatibility





Laser comes with receiver as standard.

Accessories

Standard Accessories		
	LE00796587	LR150 Laser Receiver
	LE00796588	RC30 Remote
	LE00791661	Wall Mount
	LE00834534	Laser Detection Glasses
	LE00775106	Target Plate

Standard Accessories		
	LE00784968	Clamp for Receiver

Optional Accessories		
	P-81088	Aluminium Tripod
	P-81309	4mx4 Section Aluminium Telescopic Staff