Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLEGATED REGOT	-AHON (LO) 2013/2	2015 with regard to ener	gy labelling of light
Supplier's name	e or trade mark:	Nordlux		
Supplier's addre	ess: Nordlux A/S	, Østre Havnegade	34, 9000 Aalborg, DK	
Model identifie	er: 2110561001			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	DLS
Light source cap-type		Ledmodule		
(or other electric interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para		T .
Parameter		Value	Parameter	Value
		General product	-	_
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		10	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		800 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P _{on}), expressed in W		10,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimen-	Height	210	Spectral power dis-	See image
sions without separate con- trol gear, light- ing control	Width Depth	125 220	tribution in the range 250 nm to 800 nm, at full-load	in last page

parts and non- lighting con- trol parts, if any (millime-			
tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,463 0,407
Parameters for directional light so	ources:		
Peak luminous intensity (cd)	340	Beam angle in degrees, or the range of beam angles that can be set	120
Parameters for LED and OLED ligh	nt sources:		
R9 colour rendering index value	49	Survival factor	0,00
the lumen maintenance factor	0,00		
Parameters for LED and OLED ma	ins light sources	:	
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

