## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2015146103

Lighting technology used:	LED	Non-directional or	NDLS		
		directional:			
Light source cap-type	LED module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light	Yes		
		source (CLS):			
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

## **Product parameters**

Froduct parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
0,	mption in on- 00 h), rounded st integer	30	Energy efficiency class	Е			
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	3 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 6 500			
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	30,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	-			
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimensions without	Height Width	600 600	Spectral power distribution in the	See image in last page			
separate con- trol gear, light- ing control	Depth	32	range 250 nm to 800 nm, at full-load				

parts and non-						
lighting con-						
trol parts, if						
any (millime-						
tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,312			
		nates (x and y)	0,328			
Parameters for LED and OLED li	ght sources:	1111				
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,95					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency	6			
		in McAdam ellipses				
Claims that an LED light source	_(b)	If yes then replace-	-			
replaces a fluorescent light		ment claim (W)				
source without integrated bal-		,				
last of a particular wattage.						
	1.0	C. 1	0.4			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;

