LAUFEN INSTALLATION SYSTEM

E-AW107 Electronic actuator plate, dual flush 90010.7



TECHNICAL Order no.	90010.7	Quality material	Glass
matching for	LAUFEN concealed cisterns	Weight	0,73 kg
matering for	CW102, order no. 92010.2,	Mounting acc. incl.	Support frame
	CW103, order no. 92010.3,	Mounting acc. moi.	Fastening set
	CW103, order no. 92010.3,	Mounting acc. excl.	Electronic control 100-230 V, 50-60Hz
	CW104, order no. 92010.4,	Mounting acc. exci.	order no. 89866.0
	CW103, order no. 92010.5,	Colours	020 – Glass black
	CW100, order no. 92010.0,	Colours	020 - Glass black
	CWL103, order no. 92710.3,		
	TW101, order no. 92610.1,		
	TW101, order no. 92610.1,		
Specification	Actuator plate with IR sensor		
Specification	For front operated.		
	Hygienic, touch-free infrared sensor controlled		
	WC dual flush system.		
	User recognition via IR sensors,		
	long range approx. 1500 mm or		
	short range approx. 60 mm.		
	Inviting function by corona lighting and		
	user-leading light functions.		
	Flush interval freely selectable, factory set to 24 h.		
	7 light colours can be selected.		
	External power supply to be ordered separately.		
	Button illumination activated when approached.		
	Low-noise lifting mechanism.		
	LOW HOISE IIIIIIIII IIIECHAIIISIII.		

TECHNICAL DRAWINGS / S 1 : 10



