

**Floorstanding WC rimless combination with cistern
with fixing holes for floor fixation
82896.8**



TECHNICAL DATA

Order no.	82896.8	Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2
Certified to	EN 997		for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5
Specification	Washdown for 4,5/3-l-flush, Charge 737 2 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass	Colours	see colour table
Outlet	horizontal VARIO, vertical 70 - 250 mm	SPECIFICATION TEXT	
Weight	39,5 kg	Floorstanding WC rimless washdown LAUFEN PRO N, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush) EN 997, 4,5/3-l-flush, dimensions 365 x 650 x 890 mm outlet horizontal, VARIO vertical 70 - 250 mm back to wall, concealed fixation, 2 fixing holes Special feature: concealed surfaces directing water are fully glazed throughout, open water rim, vacuum checked Further options / accessories: Surface refinement LCC, WC seat 89115.3, WC seat and cover 89095.2, 89115.0, 89115.2, WC seat and cover with automatic lowering 89095.3, 89115.1	
Accessories excl.	Seat, order no. 89115.3 Seat and cover, order no. 89095.2, 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89095.3, 89115.1	Order no. 82896.8	
Mounting acc. incl.	Fastening kit, order no. 89175.7		

TECHNICAL DRAWINGS / S 1 : 20

