

cifrecerámica

T E C H N I C A L

INFORMATION

INFORMACIÓN

T E C N I C A



**DECLARATIONS OF PERFORMANCE**



**Dear customers:**

As you know, as of 1<sup>st</sup> of July 2013, the new European Regulation for Construction Products, Nr. 305/2011, comes into force, and in order for us to adapt to it, we send you the DECLARATIONS OF PERFORMANCE, valid for the different product families.

For your information, declarations have been divided into groups:

Nr. 001-CPR-PRBR-2013-07-01. GLOSS PORCELAIN

Nr. 002-CPR-G-2013-07-01. STONEWARE

NR. 003-CPR-A-2013-07-01. WALL TILES

Nr. 004-CPR-PR-2013-07-01. MATT PORCELAIN

Nr. 005-CPR-GAD-2013-07-01. ANTISLIP STONEWARE

Nr. 006-CPR-PRAD-2013-07-01. ANTISLIP PORCELAIN

Nr. 007-CPR-PE-2013-07-01. SPECIAL PIECES

Nº 008-CPR-GPAD-2013-07-01. ANTISLIP PORCELAIN STONEWARE

Nº 009-CPR-PRF-2013-07-01. THIN THICKNESS

Nº 010-CPR-EXT-2013-11-06. PORCELAIN EXTRUDED

The said documents are available in our website,

[www.cifreceramica.com](http://www.cifreceramica.com), in section downloads/declaration of features.

(Home / Cifre Ceramica / Downloads)

In case you need a paper copy, ask your sales representative at Cifre Cerámica and you will be served in the shortest delay.



## GLOSSY PORCELAIN TILES

## TYPE 1

## DECLARATION OF PERFORMANCE

N° 001-CPR-PRBR-2013-07-01

Onda, 1<sup>ST</sup> July 2013

## 1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption  $0.5\% < E \leq 3\%$ , type 1

## 2.- Intended use.

For indoor and outdoor walls and floorings

## 3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

## 4.- System of assessment and verification of constancy of performance.

4

## 5.- Harmonised standard

EN 14411:2016

## 6.- Declared performance.

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE   | HARMONISED TECHNICAL SPECIFICATION |
|--|---|------------------------------------|
| Reaction to fire   | A1-A1 <sub>FL</sub>                                       | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP   |                                    |
| Breaking strength  | ≥ 1100 N  |                                    |
| Bond Strength/Adhesion for (N/mm <sup>2</sup> )  | > 1 Nw/mm <sup>2</sup> with cementitious adhesive type C2 |                                    |
| Thermal shock resistance   | PASS  |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>PASS  |                                    |
| Tactility :  | NDP   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.



## STONEWARE

## TYPE 2

## DECLARATION OF PERFORMANCE

N° 002-CPR-G-2013-07-01

Onda, 1<sup>ST</sup> July 2013

## 1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption  $3\% < E \leq 6\%$ , type 2

## 2.- Intended use.

For indoor floorings.

## 3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

## 4.- System of assessment and verification of constancy of performance.

4

## 5.- Harmonised standard

EN 14411:2016

## 6.- Declared performance.

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE      | HARMONISED TECHNICAL SPECIFICATION |
|--|------------------|------------------------------------|
| Reaction to fire   | A1 <sub>FL</sub> | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP              |                                    |
| Breaking strength  | ≥ 1000 N         |                                    |
| Slipperiness, as:<br>PTV SLIDER 57 CEN/TS 16165  | NDP              |                                    |
| Thermal shock resistance   | PASS             |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>NDP      |                                    |
| Tactility :  | NDP              |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.



## WALL TILES

## TYPE 3

## DECLARATION OF PERFORMANCE

N° 003-CPR-A-2013-07-01

Onda, 1<sup>ST</sup> July 2013

## 1.- Unique identification code of de product type.

Dry-pressed ceramic tiles, with water absorption E &gt; 10%, type 3

## 2.- Intended use.

For indoor walls.

## 3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

## 4.- System of assessment and verification of constancy of performance.

4

## 5.- Harmonised standard

EN 14411:2016

## 6.- Declared performance.

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE   | HARMONISED TECHNICAL SPECIFICATION |
|--|---|------------------------------------|
| Reaction to fire   | A1  | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP   |                                    |
| Bond Strength/Adhesion for (N/mm <sup>2</sup> )  | > 1 Nw/mm <sup>2</sup> with cementitious adhesive type C2 |                                    |
| Thermal shock resistance   | NDP   |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>NDP   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Cerámica S.L.

**MATT PORCELAIN****TYPE 4****DECLARATION OF PERFORMANCE**

N° 004-CPR-PR-2013-07-01

Onda, 1<sup>ST</sup> July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption  $0.5\% \geq E$ , type 4**2.- Intended use.**

For indoor and outdoor walls and floorings

**3.- Name and contact address of the manufacturer.**

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

**4.- System of assessment and verification of constancy of performance.**

4

**5.- Harmonised standard**

EN 14411:2016

**6.- Declared performance.**

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE   | HARMONISED TECHNICAL SPECIFICATION |
|--|---|------------------------------------|
| Reaction to fire   | A1-A1 <sub>FL</sub>   | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP   |                                    |
| Breaking strength  | $\geq 1300$ N   |                                    |
| Bond Strength/Adhesion for (N/mm <sup>2</sup> )  | $> 1$ Nw/mm <sup>2</sup> with cementitious adhesive type C2 |                                    |
| Thermal shock resistance   | PASS  |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>PASS  |                                    |
| Tactility :  | NDP   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.

**ANTISLIP STONWARE****TYPE 5****DECLARATION OF PERFORMANCE**

N° 005-CPR-GAD-2013-07-01

Onda, 1<sup>ST</sup> July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption  $3\% < E \leq 6\%$ , type 5**2.- Intended use.**

For indoor floorings.

**3.- Name and contact address of the manufacturer.**

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

**4.- System of assessment and verification of constancy of performance.**

4

**5.- Harmonised standard**

EN 14411:2016

**6.- Declared performance.**

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE      | HARMONISED TECHNICAL SPECIFICATION |
|--|------------------|------------------------------------|
| Reaction to fire   | A <sub>1FL</sub> | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP              |                                    |
| Breaking strength  | ≥ 1000 N         |                                    |
| Slipperiness, as:<br>PTV SLIDER 57 CEN/TS 16165  | Rd > 45          |                                    |
| Thermal shock resistance   | NDP              |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>NDP      |                                    |
| Tactility :  | NDP              |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.



**ANTISLIP PORCELAIN****TYPE 6****DECLARATION OF PERFORMANCE**

N° 006-CPR-PRAD-2013-07-01

Onda, 1<sup>ST</sup> July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption  $0.5\% \geq E$ , type 6**2.- Intended use.**

For indoor and outdoor walls and floorings

**3.- Name and contact address of the manufacturer.**

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

**4.- System of assessment and verification of constancy of performance.**

4

**5.- Harmonised standard**

EN 14411:2016

**6.- Declared performance.**

| ESSENTIAL CHARACTERISTICS   | PERFORMANCE   | HARMONISED TECHNICAL SPECIFICATION |
|---|---|------------------------------------|
| Reaction to fire  | A1 - A <sub>1FL</sub>                                       | EN 14411                           |
| Release of dangerous substance, for:<br>• Cadmium<br>• Lead<br>• Others | NDP   |                                    |
| Breaking strength   | $\geq 1300$ N   |                                    |
| Slipperiness, as:<br>PTV SLIDER 57 CEN/TS 16165                         | Rd > 45   |                                    |
| Bond Strength/Adhesion for (N/mm <sup>2</sup> )                         | > > 1 Nw/mm <sup>2</sup> with cementitious adhesive type C2 |                                    |
| Thermal shock resistance  | NDP   |                                    |
| Durability:<br>• Indoor use.<br>• Outdoor Use                           | PASS<br>PASS  |                                    |
| Tactility :   | NDP   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.

**SPECIAL PIECES****TYPE 7****DECLARATION OF PERFORMANCE**

N° 007-CPR-PE-2013-07-01

Onda, 1<sup>ST</sup> July 2013**1.- Unique identification code of de product type.**

Special pieces of dry-pressed ceramic tiles, type 7

**2.- Intended use.**

For indoor walls.

**3.- Name and contact address of the manufacturer.**

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

**4.- System of assessment and verification of constancy of performance.**

4

**5.- Harmonised standard**

EN 14411:2016

**6.- Declared performance.**

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE | HARMONISED TECHNICAL SPECIFICATION |
|--|-------------|------------------------------------|
| Reaction to fire   | A1          | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP         |                                    |
| Bond Strength/Adhesion for (N/mm <sup>2</sup> )  | NDP         |                                    |
| Thermal shock resistance   | NDP         |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>NDP |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Cerámica S.L.

**ANTISLIP STONEWARE PORCELAIN****TYPE 8****DECLARATION OF PERFORMANCE**

N° 008-CPR-GPAD-2013-07-01

Onda, 1<sup>ST</sup> July 2013**1.- Unique identification code of de product type.**Dry-pressed ceramic tiles, with water absorption  $0.5\% < E \leq 3\%$ , type 8**2.- Intended use.**

For indoor and outdoor walls and floorings

**3.- Name and contact address of the manufacturer.**

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

**4.- System of assessment and verification of constancy of performance.**

4

**5.- Harmonised standard**

EN 14411:2016

**6.- Declared performance.**

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE           | HARMONISED TECHNICAL SPECIFICATION |
|--|-----------------------|------------------------------------|
| Reaction to fire   | A1 - A <sub>1FL</sub> | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP                   |                                    |
| Breaking strength  | ≥ 1100 N              |                                    |
| Slipperiness, as:<br>PTV SLIDER 57 CEN/TS 16165  | Rd > 45               |                                    |
| Thermal shock resistance   | PASS                  |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>PASS          |                                    |
| Tactility :  | NDP                   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.



## THIN THICKNESS

## TYPE 9

## DECLARATION OF PERFORMANCE

N° 009-CPR-PRF-2013-07-01

Onda, 11 Sept 2017

## 1.- Unique identification code of de product type.

Dry-pressed ceramic tiles and thickness <7.5mm with water absorption  $0.5\% \geq E$ , type 9

## 2.- Intended use.

For indoor and outdoor walls and floorings

## 3.- Name and contact address of the manufacturer.

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

## 4.- System of assessment and verification of constancy of performance.

4

## 5.- Harmonised standard

EN 14411:2016

## 6.- Declared performance.

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE   | HARMONISED TECHNICAL SPECIFICATION |
|--|---|------------------------------------|
| Reaction to fire   | A1 - A1 <sub>FL</sub>                                     | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP   |                                    |
| Breaking strength  | $\geq 700$ N  |                                    |
| Bond Strength/Adhesion for (N/mm <sup>2</sup> )  | > 1 Nw/mm <sup>2</sup> with cementitious adhesive type C2 |                                    |
| Thermal shock resistance   | PASS  |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>PASS  |                                    |
| Tactility :  | NDP   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.

**PORCELAIN EXTRUDED****TYPE 10****DECLARATION OF PERFORMANCE**

N° 010-CPR-EXT-2013-11-06

Onda, 1<sup>ST</sup> July 2013**1.- Unique identification code of de product type.**Extruded tiles, with water absorption  $0.5\% < E \leq 3\%$ , type 10**2.- Intended use.**

For indoor and outdoor walls and floorings

**3.- Name and contact address of the manufacturer.**

CIFRE CERAMICA, S.L.

Ctra. Villarreal - Onda, Km.10 12200 ONDA (Castellón) SPAIN

**4.- System of assessment and verification of constancy of performance.**

4

**5.- Harmonised standard**

EN 14411:2016

**6.- Declared performance.**

| ESSENTIAL CHARACTERISTICS  | PERFORMANCE           | HARMONISED TECHNICAL SPECIFICATION |
|--|-----------------------|------------------------------------|
| Reaction to fire   | A1 - A1 <sub>FL</sub> | EN 14411                           |
| Release of dangerous substance, for: <ul style="list-style-type: none"> <li>• Cadmium</li> <li>• Lead</li> <li>• Others</li> </ul> | NDP                   |                                    |
| Breaking strength  | ≥ 1100 N              |                                    |
| Slipperiness, as:<br>PTV SLIDER 57 CEN/TS 16165  | Rd > 45               |                                    |
| Thermal shock resistance   | PASS                  |                                    |
| Durability: <ul style="list-style-type: none"> <li>• Indoor use.</li> <li>• Outdoor Use</li> </ul>                                 | PASS<br>PASS          |                                    |
| Tactility :  | NDP                   |                                    |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf  
of the manufacturer by

Enrique Cifre Nebot  
CEO Cifre Ceramica S.L.

# cifrecerámica