



# CM 150 AUTOMATIC




## AVAILABLE BLADES




## ACCESSORIES



## PACKAGE



## TECHNICAL CHARACTERISTICS



- For cutting, cutting and beveling in a single operation, 45° mitres, 1/2 bullnose, grooves (for safety treads) in porcelain, marble, granite, single and double fired.
- Maximum length of cut 150 cm (6").
- Maximum thickness of cut: 80 mm (3 1/8") in single pass; 90 mm (3 1/2") in double pass.
- Precise adjustability of cutting depth via micrometric lifting/lowering device.
- Maximum disc Ø 300 mm (12").

- Blade cooling via non-submersible heavy duty exterior pump and multiple water jets.
- Motor assembly with automatic feed (5 speeds).
- Sliding motor assembly with 4 adjustable PVC rollers (with bearings).
- Tilting motor group for performing mitre cuts from 0° to 47°.
- Detachable stand with adjustable feet.
- Supplied with: extension bench with square, countersquare, key kit, dressing stone, user and maintenance manual.

## MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Disc	Disc
379FUL 230	8024648011817	1	230 V 50 Hz	Single-phase	2,8 HP / 2,1 kW	2800	-	2800
379FUL 230 6	8024648014283	1	230 V 60 Hz	Single-phase	2,8 HP / 2,1 kW	3360	-	3360
379FUL 230 T	8024648014290	1	230 V 60 Hz	Three-phase	2,8 HP / 2,1 kW	3360	-	3360
379FUL 400	8024648003379	1	400 V 50 Hz	Three-phase	4 HP / 3 kW	2800	-	2800
379FUL400/6	8024648016690	1	400 V 60 Hz	Three-phase	4 HP/3 kW	3360	-	3360
379FUL 115	8024648009302	1	110 V 50 Hz	Single-phase	2,2 HP / 1,65 kW	2800	-	2800

## CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Disc	Depth	Depth	Length	Length	Table	Table	Weight	Dimensions	Weight
CM 150	300 mm 12"	80 mm 3 1/8"	55 mm 2 1/8"	150 cm 59"	∞	100x100 cm 39 3/8"x39 3/8"	215x90xh 85 cm 84 5/8"x35 1/2"xh 33 1/2"	265 Kg 584 lbs	250x105xh 110 cm 98 7/16"x41 3/8"xh 43 3/8"	310 Kg 683 lbs



# ACCESSORIES AND DIAMOND DISC FOR CM 150 AUTOMATIC



## ACCESSORIES FOR CM 150 AUTOMATIC

Part No.			Description			
<b>374RULLI</b>	8024648012593	1	Rolling side table (5 rollers) - 60 cm (2') length	75x60xh 26 cm	29 1/2" x 23 3/8" xh 10"	23.0 Kg 50.6 lbs
<b>374RULMAX</b>	8024648012609	1	Rolling side table (10 rollers) - 100 cm (3' 3") length	108x60xh 26 cm	42 1/2" x 23 3/8" xh 10"	27.6 Kg 60.8 lbs
<b>191CL05A</b>	8024648058003	1	Side square for rolling side tables	54x39xh 9 cm	21" x 15 3/8" xh 3 1/2"	3,6 Kg 7.9 lbs
<b>192SQ21A</b>	8024648011893	1	Sliding square 45° for extension bench	20x22xh 4 cm	7 7/8" x 8 3/8" xh 1 1/2"	900 gr 31.8 oz
<b>191CL03A</b>	8024648011848	1	Set-square for "CM150"	153x34xh 7 cm	60 1/4" x 13 3/8" xh 2 3/4"	12,5 Kg 27.5 lbs
<b>379BLOPIA</b>	8024648011862	1	Tile holding device for "CM150"	172x42xh 32 cm	67 3/4" x 16 1/2" xh 13"	8,6 Kg 19 lbs
<b>379SUSPE</b>	8024648011824	1	Extension bench with square for "CM150"	192x82xh 35 cm	75 5/8" x 32 1/4" xh 13 3/4"	33,6 Kg 74 lbs

## SEGMENTED DIAMOND BLADES FOR PORCELAIN AND CERAMIC TILES

Part No.					Rim height						
<b>179SET300B</b>	8024648004154	1	300 mm	12"	30 / 25,4 mm	1 3/16" / 1"	10 mm	13/32"	D 213	1 Kg 2.2 lbs	1,2 Kg 2.6 lbs

## CONTINUOUS RIM DIAMOND BLADES 45° PROFILE FOR BEVEL

Part No.			Profile			Rim height						
<b>179CC250B</b>	8024648004161	1		250 mm	10"	30 mm	1 3/16"	10 mm	13/32"	D 107	600 gr 21.2 oz	650 gr 23 oz

## DIAMOND BLADES FOR CHANNEL CUT / ANTI-SLIP GROOVE

Part No.			Profile			Rim height						
<b>179SCAN4</b>	8024648009357	1		4 mm	3/8"	250 mm	10"	30 mm	1 3/16"	D 213	2,2 Kg 4.8 lbs	2,5 Kg 5.5 lbs

